

Polycom® ViewStation® EX

Mainstream video communications for any office or conference room



Benefits

Superior video quality – Premium quality video from low bandwidth to high with support for standards based H.264 and ITU 60 fields

Optimal viewing – Simultaneously supports two video monitors for near and far side views and a third XGA video output for high-resolution monitor or projector

Extended call options – Supports up to 2 Mbps IP and 512 Kbps ISDN, audio-add over analog telephone and optional private networks (V.35 RS-530, RS-449, with RS-366 dialing)

See presenter and live, high-resolution multimedia presentation – Add high resolution XGA content and PC audio while still viewing the presenter

Security you can trust – Optional internal encryption provides security via standard-based, NIST/FIPS validated AES support - up to 2 Mbps for point-to-point or multipoint calls

Choice of single or dual high resolution displays – For a natural meeting environment. Coupled with the high fidelity audio system which delivers 270W of total power, with a powerful amplifier, subwoofer, and two (2) satellite speakers

ViewStation EX delivers enhanced capabilities to mainstream video communications.

With support up to 2 Mbps over IP, dual 10/100 Ethernet support, PVEC for concealing real-world network packet loss and multicast streaming capabilities, the ViewStation EX is ideal for organizations transitioning to IP networks or with mixed IP/ISDN environments. Optional network support for ISDN (up to 512 Kbps) and private networks (V.35, RS-530, RS-449, with RS-366 dialing) as well as options for internal MCU and AES encryption (NIST/FIPS validated) allow the EX performance to expand as your needs grow.

With standard-based video quality (H.264 and ITU 60 fields), support for simultaneous dual monitors and a projector and a robust feature set including analog telephone support and RS-232 control/data port, the ViewStation EX delivers all the video conferencing capabilities you need, and then some.

Going beyond face-to-face meetings, laptops can be quickly connected to the EX to make sharing PC audio and high-resolution (XGA) content as easy as pushing a button.

The ViewStation EX is available with the flexible Polycom Media Center, which offers high-end performance, large displays and precision audio create a quality video meeting environment, anywhere you need it, quickly and easily. Choose a single display for small to mid-sized applications or dual displays (XGA/TV grade) for sharing high-resolution meeting data from remote or local viewers.

The quality of the ViewStation EX. The power of Polycom conferencing and collaboration solutions

With integrated video, voice, data, and Web capabilities, only Polycom solutions let you connect, conference, and collaborate any way you want. It's our commitment to making distance communications as natural and interactive as being there. Work faster, smarter, and more efficiently with the Polycom ViewStation EX and other Polycom conferencing and collaboration solutions.

HOWARD[™]
TECHNOLOGY SOLUTIONS

For more information visit www.Howard.com or call us at 888.912.3151

Video

Connect. Any Way You Want.

Polycom ViewStation EX Specifications

User Interface

- User-friendly graphical interface
- Customizable home screen
- Custom logo on main screen
- Administrator controlled speed dial numbers accessible from custom logo
- Kiosk mode for custom applications
- Speed Dial List
- Alert Signal on home page
- Keypad audio dialing confirmation
- Do Not Disturb (On/Off)
- Web interface
- Picture-in-Picture (PIP) On/Off, Automatic

Remote Control

- Enhanced, grip-sensitive remote control
- Quick buttons for most common tasks
- Color-coded buttons grouped by functionality

Video Features

- Intelligently selects frame rate and video algorithm for best performance video
 - Up to 30 fps and 60 fields per second
- Automatic VCR recording of all endpoints based on the person who is talking
- Automatic Picture-in-Picture (PIP)
- See graphics content and far video on a single monitor
- MGC™ Click & View™ for individual screen layouts in MGC bridge calls

Video Standards & Annexes

- H.261: D
- H.263+: F, I, J, L, N, T
- H.263++: U, W
- H.264
- ITU 60 fields per second: Letter-box

Video Inputs: Main Camera + 2 Connectors

- 1 x S-Video; 4-pin mini DIN (Document camera)
- 1 x Composite; RCA/Phono (VCR)

Video Outputs: 5 Connectors

- 1 x S-Video; 4-pin mini DIN (Main monitor)
- 1 x Composite; RCA/Phono (Main monitor)
- 1 x S-Video (Second monitor)
- 1 x Composite; RCA/Phono (VCR)
- 1 x XGA (Graphics display)

Video Formats

- NTSC / PAL
- Graphics: SXGA, XGA, SVGA, VGA

Video Resolution

- Interlaced video (60/50 fields for NTSC/PAL): Letter-box
- 4CIF (704 x 576)
- CIF (352 x 288)
- QCIF (176 x 144)
- SQCIF (128 x 96)
- Display aspect ratios: 4:3

Main Camera

- Ultra-quiet, ultra-fast action pan/tilt/zoom (PTZ)
- Tilt Range: +/- 25° (Up/Down)
- Pan Range: +/- 100° (Left/Right)
- Zoom: 12x Zoom (10x optical & 1.2x digital); f=4.2 to 42mm
- Horizontal field of view: 65°
- Total horizontal field of view: 265°
- Auto focus
- Automatic white balance
- Camera presets: 20
- Local camera 10; Far-end camera 10
- Voice activated camera positioning to 10 presets

Audio Features

- Full-duplex audio
- Instant Adaptation Echo Cancellation
- Automatic Gain Control (AGC) – voice activated
- Automatic Noise Suppression (ANS)
- Built-in tonal speaker test
- Real-time audio level meter
- Audio mixer: Mic, VCR, telephone, line-in
- Ability to talk over VCR audio

Audio Protocols

- 7 kHz bandwidth with G.722.1, G.722 on IP/ISDN
- 3.4 kHz bandwidth with G.711, G.728 on IP/ISDN

Audio Inputs: 5 Connectors

- 1 x RJ-9 to microphone arrays
- 2 x RCA input for VCR
- 1 x RCA input for mixer
- 1 x RJ-11 for analog speaker telephone
- Integrates with Polycom Vortex® installed voice products

Audio Outputs: 5 Connectors

- 2 x RCA for main audio
- 2 x RCA for VCR record
- 1 x RJ-11 for analog speaker telephone
- Integrates with Polycom Vortex installed voice products

Digital Tabletop Microphone Array

- 360 degree voice pick-up
- Cardioid elements per microphone array: 3
- Integrated mute button
- Can be mounted to ceiling or wall
- Number of microphone arrays in base unit: 1
- Maximum number of microphone arrays: 2

People+Content™ Collaboration

- Receive or Transmit dual images (View/Send people and high-resolution content simultaneously)
- Dual audio (Transmits audio from room microphones and laptop simultaneously)
- Supports IP, ISDN and Serial calls
- Supports People+Content dual streams from any endpoint (not just host site)
- Maximum graphics resolution: 1280 x 1024, 60 Hz Input
- 1280 x 1024, 60 Hz Output
- Table-top audio input for laptop*
- Second table-top projector output*
- Triple 10/100 table-top Ethernet hub*

Other Collaboration Solutions

- PC Presents™ for Microsoft® PowerPoint®
- Polycom SNAP™
- T.120 Microsoft NetMeeting® support over ISDN calls
- Streaming in and out of a call compatible with Apple® QuickTime®, Cisco® IP/TV

Content Resolutions

- SXGA (1280 x 1023), XGA (1024 x 768), SVGA (800 x 600), VGA (640 x 480)
- Up to 4CIF with motion
- Up to 16CIF still images (H.263)
- Up to 4CIF H.261 Annex D still images

Network Features

- Automatic IP/ISDN calling
- Polycom OneDial™ intelligent call management attempts call on preferred network (IP or ISDN) and automatically rolls over to secondary network if needed
- Downspeeding over IP and ISDN
- IP address conflict warning
- Maximum call length digital timer
- Auto SPID detection and configuration
- Software upgradeable Inverse Multiplexer (IMUX)
- PathNavigator™ support for easy call placement and network cost optimization
- TCP/IP, DNS, WINS, DHCP, ARP, HTTP, FTP, Telnet
- SNMP for enterprise management
- T120 interface for Microsoft NetMeeting
- Chair control from endpoints or host systems on IP and ISDN

Bandwidth

- Maximum Data Rate IP or Serial: Up to 2 Mbps
- Maximum Data Rate ISDN: Up to 512 kbps

Network Interfaces Supported

- Ethernet port: Dual (10/100 Mbps)
- Integrated analog speaker phone for audio add-in
- ISDN BRI (Basic Rate Interface) Quad BRI*
- Serial Network Interface (V.35/RS-530/RS-449 with RS-366 dialing)
- Wireless LAN support via Ethernet port*
 - Compliant with IEEE 802.11b or 802.11g
 - Support for 64-bit to 128-bit encryption (WEP)
 - Infrastructure or ad hoc mode

Conference on Demand

- Initiates unscheduled MGC calls from the endpoint
- Utilizes Polycom Office™ (PathNavigator and MGC)
- Dials all participants simultaneously

Embedded MultiPoint

- Embedded MultiPoint Capacity: 5 sites (4 IP/ISDN sites + 1 telephone)*
- Supports mixed multipoint calls: IP, ISDN, analog telephone
- Supports IP and analog telephones
- Automatic IP and ISDN MP Downspeeding
- Automatic mixed IP/ISDN downspeeding
- Dial-in and Dial-out during MP calls
- Continuous presence - see all locations
- Voice switched - view current speaker
- Automatic MPPlus presentation modes to automatically switch between presenter and continuous presences modes
- Cascading up to 14 sites (10 IP, ISDN and mixed sites + 4 telephones)
- Password protection for incoming calls
- Audio bridge: 5 sites (4 IP + analog)

Quality of Service and Experience – iPriority™

- Video and Audio Error Concealment
- IP Precedence (ToS)
- Differserv DSCP (CoS)
- Dynamic Bandwidth Allocation
- Proactive Network Monitoring
- Packet and jitter control
- Network Address Translation (NAT) support
- Automatic NAT discovery
- Configurable video/audio/FEC service value
- Asymmetric speed control
- TCP/UDP fixed-port firewall support
- Lip synchronization
- Echo cancellation and suppression
- Auto gatekeeper discovery
- Automatic gateway dialing profiles
- Specify outbound call routing for gateway/ISDN
- Closed captioning and text chat support both in and out of calls

Security

- COMSEC tested by Titan Systems, Information Security Systems Division, and independently validated to operate with approved government encryption technologies
- KG-194/KIV-7 encryptor support with on screen and address book dialing
- Account validation number entry
- Secure password authentication
- Unique factory default passwords
- Administrator password
- H.243 MCU password
- Do not disturb control for point-to-point calls
- Auto-Answer Point-to-Point (On/Off)
- Password protect individual menu screens
- SNMP security alerts for failed and successful password authentication attempts
- Ability to disable remote interfaces: FTP, Telnet, HTTP, SNMP
- Ability to disable mixed network calls

Embedded Encryption

- Advanced Encryption Standard (AES)*
- FIPS validated by National Institute of Standards & Technology (NIST) certified agency
 - 128-bit key length
 - Standard-based AES H.235 version 3 (IP)
 - Standard-based AES H.233/H.234 (ISDN/Serial)
 - Maximum Encrypted bandwidth: 2 Mbps
 - IP, ISDN, Serial
- Automatic key generation and exchange
- Supported in People+Content
- Supported in point-to-point and multipoint calls

Directory Services

- 10,000+ number global directory*
- 1,000+ number local directory
- Limitless multipoint entries

- Live address book with Polycom Global Directory Services automatically and quickly updates directory with address changes, new endpoints, or systems being turned off*
- Polycom Global Directory Services integrates with Active Directory/LDAP*
- Automatic ISDN localization of calls

System Management

- SNMP management
- Diagnostics and software upgrades via PC, LAN
- Software upgrades via ISDN call
- Integrated remote Web management
- Remote administrator video-only monitoring of room or calls from integrated Web server (enabled/disabled from endpoint for security)
- Place a call from Web interface
- System configuration from Web interface
- Call Detail Record (CDR) – Reports calls made from the system along with call statistics
- Web interface for viewing CDR data
- Downloadable CDR files for processing
- Account number validation at call initiation integrated with Polycom Global Management System™ for billing purposes*
- Administrator-configurable dialing speeds
- Complete support for The Polycom Office:
 - Polycom Global Management System*
 - Polycom OneDial*
 - Polycom PathNavigator*
 - Polycom Conference Suite*
 - Polycom MGC*

RS-232 data port

- Control port for custom integration with remote devices such as Crestron and AMX control systems
- Communication port for transmission of serial data (e.g. medical devices) over ISDN calls

Other ITU-Supported Standards

- H.221 communications
- H.224/H.281 far-end camera control
- Annex Q standard for FECC in H.323 calls
- H.225, H.245
- H.231 in multipoint calls
- H.331 broadcast over Serial Network Interface*
- Bonding, Mode 1

Language Support

- Number of Languages Supported: 9
 - Chinese, English, French, German, Italian, Japanese, Norwegian, Portuguese, Spanish
- Translated documentation**
- Translated user interface
- Translated keypad audio dialing confirmation
- Translated web interface
- Translated remote control

Electrical

- Auto sensing power supply
- Operating voltage/power: 90-260 VAC, 47-63 Hz/60 watts

Environmental Specifications

- Operating Temperature: 0 to 40° C
- Operating Humidity: 10 to 85% R.H. non-condensing
- Non-Operating Temperature: -40 to 70° C
- Non-Operating Humidity (Non-condensing): 10 to 90%

Physical Characteristics

- Base Unit Dimensions (WxHxD): 33 x 15 x 23 cm
- Base Unit Weight: 2.7 kg / 6.0 lbs

Warranty

- Parts and labor: One-year

* Optional



HOWARD
TECHNOLOGY SOLUTIONS

888.912.3151
601.399.5077 (fax)
www.Howard.com