

T24 LIBRARY: WORRY FREE, BUDGET FRIENDLY BACKUP

Back up data without worry, thanks to the Spectra T24 LTO library. The T24 lets you automate backup using proven, reliable LTO technology, without break-ing the budget.. The Spectra T24 library uses only 2U—a few inches—of rack space to support up to 2 LTO drives and 24 LTO tapes, storing up to 19.2 TB of compressed data.

With the Spectra T24 library you:

Lower Cost with an affordable library that can expand to accommodate more data

- Remote management interface through a web browser
- Easily and affordably increase capacity by adding drives and slots
- Includes Backup Exec QuickStart software from Symantec

Reduce Risk with secure automated data protection that gives you worry-free backup using proven designs and highly reliable LTO drives and tapes

- Highly reliable scheduled backups
- Proven LTO technology
- Backed by SpectraGuard, the best support team in the industry

Save Time with the T24 by not manually swapping and tracking tapes, and kicking off backup processes

- Less than an hour to install and set up
- Compatible with every major operating system
- Runs with all major backup packages

SPECTRA LOGIC



Capacity

Media Slots	12 or 24
Tape Drives	1 or 2 LTO-2/3 Half-Height Drives
Native Capacity	4.8TB LTO-2 (200 GB Uncompressed/ Cartridge) 9.6 TB LTO-3 (400 GB Uncompressed/ Cartridge)
Media Magazines	2 Magazines with 12 slots per magazine
Entry/Exit Port	Single slot

Throughput

Half-Height Drive	LTO-2 (24MB/s uncompressed) 86GB/HR/Drive LTO-3 (60MB/s uncompressed) 216 GB/HR/Drive
--------------------------	--

Connectivity

Robotics Control and Data Path Management	LVD SCSI 10/100 Ethernet
--	--------------------------

Management and Support

Remote Management	Remote management interface through a web browser
--------------------------	---

Reliability

MCBF (Mean Cycles Between Failure)	500,000 Cycles
MTBF (Mean Time Between Failure)	130,000 Hours (Without FRUs) 90,000 Hours (With FRUs)

Physical Specifications

Height	2U Standard Rack/ 3.5"/ 8.9cm
Width	17.6"/44.7cm
Depth	29.1"/74cm

SPECTRA LOGIC

Environmental

Operating Temperature	+10°C to +35°C (Non-Condensing)
Non-operating Temperature	-30°C to +60° 9Non-Condensing
Operating Humidity	20% to 80% Relative Humidity (Non Condensing)

Power

Specifications	Requires a 110/220 Volt power Connection
----------------	--

All specifications subject to change without notice

