

AXIS P3224-V Mk II Network Camera

Streamlined and versatile HDTV 720p fixed dome

AXIS P3224-V Mk II is a streamlined fixed dome that provides HDTV 720p video. It features a varifocal lens and remote zoom and focus, which eliminates the need for hands-on fine tuning. Equipped with WDR – Forensic Capture to handle scenes with strong variations in light as well as Lightfinder technology for exceptional light sensitivity, this versatile camera provides outstanding video quality in both strong and poor light conditions. It supports Axis Zipstream technology that significantly reduces bandwidth and storage requirements.

- > **HDTV 720p video quality**
- > **Remote zoom and focus**
- > **Axis Lightfinder technology**
- > **WDR – Forensic Capture**
- > **Axis Zipstream**



AXIS P3224-V Mk II Network Camera

| | | |
|--|---|---|
| Camera | | Notification: email, HTTP, HTTPS, TCP and SNMP trap Overlay text |
| Image sensor | Progressive scan RGB CMOS 1/3" | Data streaming Event data |
| Lens | Varifocal, 2.8–10 mm, F1.6 Horizontal field of view: 90°–34° Vertical field of view: 48°–20° Remote focus and zoom, P-Iris control, IR corrected | Built-in installation aids Remote zoom, remote focus, pixel counter |
| Day and night | Automatically removable infrared-cut filter | General |
| Minimum illumination | HDTV 720p 25/30 fps with WDR – forensic capture and Lightfinder: Color: 0.18 lux at 50 IRE, F1.6 B/W: 0.04 lux at 50 IRE, F1.6 HDTV 720p 50/60 fps: Color: 0.36 lux at 50 IRE, F1.6 B/W: 0.08 lux at 50 IRE, F1.6 | Casing IP52-rated, IK08 impact-resistant, polycarbonate casing with hard-coated dome and dehumidifying membrane Encapsulated electronics and captive screws Color: white NCS S 1002-B For repainting instructions of casing and impact on warranty, contact your Axis partner. |
| Shutter time | 1/66500 s to 1 s | Mounting Mounting bracket with holes for junction boxes (double-gang, single-gang, and 4" octagon) and for wall or ceiling mount ¼"-20 UNC tripod screw thread |
| Camera angle adjustment | Pan ±180°, tilt -5 to +85°, rotation ±95° | Sustainability PVC free |
| Video | | Memory 512 MB RAM, 256 MB Flash |
| Video compression | H.264 Baseline, Main and High Profile (MPEG-4 Part 10/AVC) Motion JPEG | Power Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 2, max 4.8 W, typical 3.5 W |
| Resolution | 1280x960 to 160x90 | Connectors RJ45 10BASE-T/100BASE-TX PoE |
| Frame rate | With WDR: 25/30 fps with power line frequency 50/60 Hz Without WDR: 50/60 fps with power line frequency 50/60 Hz | Storage Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com |
| Video streaming | Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264 | Operating conditions 0 °C to 50 °C (32 °F to 122 °F) Humidity 10 to 85% RH (non-condensing) |
| Multi-view streaming | 2 individually cropped out view areas | Storage conditions -40 °C to 65 °C (-40 °F to 149 °F) |
| Pan/Tilt/Zoom | Digital PTZ, preset positions | Approvals EMC EN 55022 Class B, EN 61000-6-1, EN 61000-6-2, EN 55024, EN 50121-4, IEC 62236-4, FCC Part 15 Subpart B Class A and B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN32 Class B, KN35 Safety IEC/EN/UL 60950-1 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14 IEC 60068-2-6 (vibration), IEC 60068-2-27 (shock), IEC 60068-2-78, IEC/EN 60529 IP52, IEC/EN 62262 IK08 Network NIST SP500-267 |
| Image settings | Compression, color, brightness, sharpness, contrast, local contrast, white balance, exposure control (including automatic gain control), exposure zones, fine tuning of behavior at different light levels, WDR – forensic capture: up to 120 dB depending on scene, text and image overlay, mirroring of images, privacy masks Rotation: 0°, 90°, 180°, 270°, including Corridor Format | Dimensions Height: 101 mm (4 in) ø 149 mm (5 7/8 in) |
| Network | | Weight 550 g (1.2 lb) |
| Security | Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management, brute force delay protection | Included accessories Installation Guide, Windows decoder 1-user license, mounting bracket, cable gasket, Resistorx® T20 L-key, drill template, connector guard |
| Supported protocols | IPv4, IPv6 USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3(MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP | Optional accessories AXIS ACI Conduit Bracket B, AXIS ACI Conduit Adapters, AXIS T94K01L Recessed Mount Kit, AXIS T94K01D Pendant Kit, AXIS Skin Cover C, Black, AXIS Mounts, Smoked dome For more accessories, see www.axis.com |
| System integration | | Video management software AXIS Companion, AXIS Camera Station, Video management software from Axis Application Development Partners available on www.axis.com/vms |
| Application Programming Interface | Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S and ONVIF Profile G, specification at www.onvif.org | Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese |
| Analytics | Included AXIS Video Motion Detection, active tampering alarm Supported AXIS Guard Suite including AXIS Motion Guard, AXIS Fence Guard, and AXIS Loitering Guard, AXIS Perimeter Defender Support for AXIS Camera Application Platform enabling installation of third-party applications, see www.axis.com/acap | Warranty Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty |
| Event triggers | Analytics, edge storage events, virtual inputs through API | |
| Event actions | Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload | |

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).

Environmental responsibility:
www.axis.com/environmental-responsibility