



*All images are simulated

65" Full HD Resolution Panel

- All-in-one solution with 65" full HD panel

Up to 10 touch points (simultaneous)

- Ideal function for classrooms
- You can write from both right and left sides

Stereo speakers (20W total)

- 20W stereo speakers facilitates delivery of bold sound directly to your audience

Front HDMI and use inputs

- Simply plug in your computer with HDMI and USB for touch control and you are ready to go

Both Windows® and Mac OS® compatible

- Greater user versatility

Additional convenient features



- LAN port for control, OPS slot, and magnetic stylus pens



YouTube



HILF65101



LED PANEL

Diagonal Size	64.53" (163.9 cm)
Display Resolution (Max.)	1,920 x 1,080 (FHD)
Brightness (average)	350 cd/m ²
Viewing Angle	H: 176° / V: 176°
Contrast Ratio	5,000 : 1 (typical)
Supported Colors	16.7M colors (8-bit)
Response Time	6.5ms (gray to gray)
Display Frame Rate	60Hz (actual)
Installation	Landscape orientation

TOUCH

Detect Area (H x V)	56.24" x 31.63" (1428.5 mm x 803.5 mm)
Detection Method	Infrared blocking detection method
Touch Tool	Hand or other solid object
Accuracy	±2mm
Response Time	<12ms
Available Touch Point	10 points
Operating Systems	Windows 7, 8, 10/ Mac OS 10.10-10.12
PC Connector	USB

SIGNAL CONNECTIVITY

Video Input	HDMI x 3 (front x 1, rear x 1, only for inside OPS x 1), display port x 1, VGA x 1
Audio	RCA speaker out (R/L), stereo mini line out, stereo mini Input
Communication Port	RJ45 (LAN), RS-232C (D-sub 9-pin), USB-B (only for touch control) x 1 (either front or rear port is workable)
Front Input	HDMI x 1 (as specified in "Video Input"), USB-B (only for touch control as specified in "Communication Port") x 1, USB-A x 1

MECHANICAL

Dimensions Landscape	59.29" x 35.51" x 3.62" (1506 mm x 902 mm x 92 mm)
Weight (Mass)	97.6 lbs. (43 kg.)
VESA Mount	400 mm x 200 mm, M8 screw
Front Glass	Tempered glass 4.0t (anti-glare type)

ELECTRICAL

Power Requirement	100 - 240V AC, 50/60 Hz
Power Consumption	Max. 185W
Power Consumption (Standby)	<0.5W
Speaker Output	10W + 10W Stereo (8-ohms)

ENVIRONMENTAL

Operating Temperature	0 - 40 °C (32 - 104 °F)
Storage Temperature	-20 - 60 °C (-4 - 140 °F)
Operating Humidity	20% to 80% RH (no condensation)

OSD FUNCTIONS


OSD Language Function	English / Français / Deutsch / Spanish / Portuguese / Italiano / Danish / Swedish / Norwegian / Suomi / Russian / Polish / Turkish / Hungarian / Chesky / Korean
OSD Key Lock Function	Support

ACCESSORIES

Supplied	Magnetic stylus pen x 2, remote control, HDMI Cable, USB cable, power cable, CD (user manual, installation manual, touch driver)
-----------------	--

CERTIFICATIONS

Standard	QAS, RCM, CB, RoHS, FCC, NRTL
-----------------	-------------------------------



HI0545-06/17

©2017 Hitachi America, Ltd. All Rights Reserved. Design and specifications are subject to change without notice. Microsoft, Encarta, MSN, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Mac OS® is registered trademarks of Apple Inc. HDMI, High-Definition Multimedia Interface, and the HDMI logo are trademarks or registered trademarks of HDMI Licensing, LLC in the United States and/or other countries. Crestron® is a registered trademark of Crestron Electronics, Inc. All other trademarks and registered trademarks are the property of their respective owners in the United States and/or other countries.

Hitachi America, Ltd.

Toll Free: 1.800.HITACHI • Email: dmd.info@hal.hitachi.com

Web: hitachi-america.us/IFPD

