Flexible Thin Client

Endless Possibilities

SC-T35

The ViewSonic® SC-T35 Thin Client is perfect for businesses looking for cost-effective and flexible solutions for their virtual desktop computing needs. Equipped with Texas Instruments DM8148 CPU and ARM Linux OS, the SC-T35 is optimized for all of the major remote networking protocols including Citrix® ICA/HDX, software accelerated PCoIP,™ and Microsoft® RemoteFX™–making it a versatile virtualization solution with endless possibilities. With a slim and compact design, the SC-T35 easily attaches to your VESA-ready monitor with the included VESA mounting bracket, and also provides dual digital outputs for driving dual 1080p displays. In addition to saving space, the SC-T35 also saves on energy with an eco-friendly design that consumes just 8W of power and uses up to 90%* less energy than standard PCs. ViewSonic's Thin Clients are the smart choice for optimizing your virtual desktop deployment.

Easy Deployment and Management

Deploy users up to 5 times faster than traditional PC-based clients, and enjoy ongoing simplified management without the need for constant patches and system updates.

Powerful Computing Combination

Texas Instruments DM8148 ARM and ARM Linux Operating System provide the power and flexibility to support multiple network protocols including Citrix ICA/HDX, PCoIP for VMware,® and Microsoft RDP with RemoteFX.

Flexible Design

Future-proof your network with this flexible thin client and rest assure that you will be supported even if your virtualization needs change later. This is the go-to thin client for mainstream VDI applications.

Low Total Cost of Ownership

From the low initial expenditure cost, to the long-life solid state design, and the ultra low 8-watt typical power consumption, the SC-T35 is the definition of efficiency.

Flexible Thin Client

SC-T35

DVI-D

Power Button

DVI-I

Audio In

Headphone

LAN

USB x4

DC Power In

Front   Back

Applications

- Education and SMB looking for lower TCO computing solutions

- Enterprise Thin / Zero Client Computing (Citrix, VMware, Microsoft)

- Financial and Medical customers with enhanced security requirements

Stand / VESA Mounting Bracket

Optional Accessories

USB Keyboard & Mouse....................................VMP10B_KM1US05
Wireless USB Adapter WPD-100

Specifications

PART #		SC-T35_BK_US_0
CORE	CPU Processor Type	TI DM8148 ARM
	CPU Processor Speed	1.0 GHz
GRAPHICS	Graphic Chipset	None
	Resolution	1920x1080 (1920x1200 supported with Pixel Clock <165Mhz)
MEMORY	System	DDR3 1GB @ 800MHz
	Storage	512MB Flash
SOFTWARE	Operating System	Linux
	Management	ViewSonic Device Manager / ViewSonic Client Setup
	Protocols	Citrix ICA/HDX 12.2.3
		VMware View 5.01,
		Microsoft RDP7.1 with RemoteFX
	Network Standard	Gigabit Ethernet
		DHCP
		SSL
		PPPoE
		Wake on LAN
COMMUNICATION	Ethernet	10/100/1000 MB
	Wireless	802.11 b/g/n with optional wireless USB adapter (WPD-100)
CONNECTOR	USB	USB 2.0 (x2 front, x2 rear)
	Video Out	DVI-D (x1), DVI-I (x1)
	LAN	RJ45 (x1)
	Microphone In	3.5mm mini jack (x1)
	Headphone	3.5mm mini jack (x1)
	Power	DC In

POWER	Voltage	5V DC; 3A, 15W
	Consumption	8W (typ)
OPERATING CONDITIONS	Temperature	32–104ºF (0–40ºC)
	Humidity	10–90% (non-condensing)
DIMENSIONS (W x H x D)	Physical with stand	1.6 x 5.6 x 4.1 in. / 39.5 x143 x 103 mm
	Packaging	7.9 x 5.0 x 6.2 in. / 200 x 128 x 157 mm
WEIGHT	Net	1.0 lb. / 0.5 kg
	Gross	2.2 lb. / 1.0 kg
WALL MOUNT	VESA®	100mm x 100mm
REGULATIONS		FCC, ENERGY STAR®, EPEAT Silver, WEEE, RoHS compliant, REACH compliant
RECYCLE/DISPOSAL		Please dispose of in accordance with local, state or federal laws.
WARRANTY		3-year limited warranty on parts and labor
COUNTRY OF ORIGIN		Taiwan

What's in the box?

SC-T35 Thin Client, power cord, power adapter, DVI-I to VGA adapter, Stand/VESA mounting bracket, Quick Start Guide, ViewSonic Wizard CD

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

HOWARD™ | TECHNOLOGY

www.howardcomputers.com | (888) 912-3151