

LifeBook T4215 Tablet PC

The comfort and ease of a traditional notebook combined with the versatility of a tablet best describes the eye-catching LifeBook[®] T4215 Tablet PC. Built-in modular bay, integrated wireless access, and the latest Intel[®] Centrino[®] Duo Mobile Technology or optional Wi-Fi[®] certified Atheros Super AG[®] means you can instantly input and access information whenever, wherever, and however needed.

BENEFITS

Product Versatility

The LifeBook T4215 Tablet PC is not only perfect for project-based application users that require the power of inking or easy pen-driven navigation, but also for mobile professionals who must have a keyboard and integrated media drive all included in one unit. Taking advantage of the industry-first bi-directional swivel hinge, you can easily transform this standard notebook into a tablet configuration by rotating (in either direction) and folding the screen. Collect data efficiently and accurately using the stylus to make handwritten notes and drawings with digital ink. To enter data using the keyboard, tilt up and rotate the screen (follow the arrow indicator) to a notebook configuration. The stylus and active digitizer continue to work in the notebook configuration.

Mobile Productivity

You can choose one of three 12.1" displays with active digitizer to perfectly fit your business needs: An indoor XGA TFT, an indoor/outdoor XGA TFT, or an indoor SXGA+ TFT display. With Intel Centrino Duo Mobile Technology, and the full power and enhanced functionality of Genuine Windows XP Tablet PC Edition, or Windows Vista™ Business, the LifeBook T4215 Tablet PC delivers mobility, convenience, and increased productivity. In the field, use the stylus to easily navigate forms-based or menu-driven applications. Use the powerful inking capabilities to take notes or capture a signature, then easily convert your handwritten notes into typed text. When you return to your hotel or office, use the keyboard in standard notebook mode to incorporate your notes into a business proposal or summary report.

Boundless Connectivity

Connect to your office network or the Internet with Wi-Fi Certified integrated Ethernet LAN, modem, wireless LAN (802.11a/b/g), or optional Atheros Super AG wireless LAN. The LifeBook T4215 Tablet PC comes equipped with diversity antennas mounted in the display panel to achieve high data transfer rates and strong connection reliability. If you use a Bluetooth-enabled cellular phone or PDA, your LifeBook T4215 Tablet PC can be equipped with integrated Bluetooth (version 2.0) wireless technology for data synchronization and swapping images.


Maximum Usability

The LifeBook T4215 Tablet PC is very versatile: Use it in notebook mode or in tablet mode, as your needs dictate. The built-in modular bay allows you to have a second battery for extra-long work days and plane trips. It can also accommodate one of the modular bay media drives to handle all of your digital media needs: DVD movies, CD audio, or burning data onto CDs or DVDs. While in tablet mode, the exclusive patent pending BayLock[™] utility automatically locks the media drive door closed and stops the drive from spinning, protecting both the drive and the media inside from accidental ejection or potential damage. This is a key feature for the mobile tablet PC user. All of this functionality comes in a tablet PC that weighs as little as 4.3 lbs., and still manages to house an array of ports that allow you to connect peripherals directly. An optional port replicator with hot-docking capability gives you immediate access to desktop peripherals.

Uncompromised Security

The LifeBook T4215 Tablet PC takes security to the next level. Featuring a cutting-edge fingerprint sensor, Trusted Platform Module (TPM) 1.2, dedicated Smart Card slot, LifeBook Application/Security Panel, two-level hard drive password, BIOS-enabled Computrace/LoJack theft recovery service option, and security lock slot, you can be confident that your data is safe and secure.

FUĴITSU



OVERVIEW

- Dual functionality for notebook and tablet use
- Intel Centrino Duo Mobile Technology for groundbreaking performance and extended battery life
- Industry-first bi-directional LCD hinge
- Built-in modular bay supports media drive or bay battery
- Integrated Wi-Fi Certified 802.11a/b/g wireless LAN, modem, and Gigabit Ethernet; optional Bluetooth 2.0 wireless
- Most comprehensive security features including integrated fingerprint sensor, embedded TPM 1.2, dedicated Smart Card slot, Security Application Panel, two-level hard drive password, BIOS-enabled for Computrace/LoJack theft recovery service, and security lock slot

Operating Systems	Genuine Windows [®] XP Tablet PC Edition 2005 with Microsoft [®] Office OneNote [®] 2003; or Genuine Windows Vista™ Business with Microsoft [®] Office OneNote [®] 2007
Software	Microsoft® Experience Pack for Tablet PC (XP Tablet PC Edition only), Google Desktop (Vista Business model only), Adobe® Reader®, Norton Internet Security ¹ , Fujitsu Display Controls, Fujitsu HotKey Utility, Fujitsu Security Application Panel, Fujitsu Driver Update Utility, Softex OmniPass, Shock Sensor Utility, TPM Drivers and Application CD
	Note 1: Microsoft [®] Office OneNote [®] 2003/2007 requires product activation
Optional Software	Depending on your system configuration, you may also receive the following: Microsoft [®] Office Small Business Edition 2003/2007, Bluetooth Utility, CyberLink PowerDVD™, Roxio Digital Media SE (on XP Tablet PC model) or Roxio Easy Media Creator (on Vista Business model), CyberLink PowerProducer™

Key Specifications

Processor		2 Duo Processor T5500 (1.66 GHz, 2 MB L2 cache, 667 MHz FSB)		
	Intel [®] Core [™] 2 Duo Processor T5600 (1.83 GHz, 2 MB L2 cache, 667 MHz FSB)			
	Intel [®] Core [™] 2 Duo Processor T7200 (2 GHz, 4 MB L2 cache, 667 MHz FSB)			
	Intel [®] Core [™] 2 Duo Processor T7400 (2.16 GHz, 4 MB L2 cache, 667 MHz FSB)			
Chipset	Intel [®] 945GM			
Memory	Two DIMM slots; max. 4 GB, 200-pin SO-DIMM, DDR2 667 MHz with dual channel suppor			
Display	LCD	12.1" XGA TFT indoor (Transmissive) display with wide viewing angles; 12.1" XGA TFT indoor/outdoor (Transmissive) display with wide viewing angles; 12.1" SXGA+ TFT indoor (Transmissive) display		
	Video			
	Controller	Intel® Graphics Media Accelerator 950; Dynamic Video Memory Technology (DVMT) responds to application requirements and efficiently allocates the proper amount of system memory (up to 224 MB) for optimal graphics and system performance.		
	Resolution	Maximum internal display resolution: 1024 x 768, 16M colors; external monitor resolution: 1600 x 1200, 16M colors; simultaneous display resolution: 1024 x 768		
Digitizer	Electromagnetic (Active)			
Hard Drive ²	120 GB, 100 GB, 80 GB, 60 GB, or 40 GB; 5400 rpm; Serial-ATA 150; shock-mounted;			
	two-level password protection; Shock Sensor Utility locks the hard drive when detecting			
	sudden impa	act, freefall, or vibration (must install this application from the included CD)		
Optical Drive		ude: Modular Dual-Layer Multi-Format DVD Writer (2.4x DVD-R/+R DL,		
		R, 4x DVD-RW/+RW, 3x DVD-RAM, 8x DVD-ROM, 24x CD-R, 10x CD-RW,		
		<i>I</i>), or, Modular DVD/CD-RW Combo Drive (8x DVD-ROM, 10x CD-RW,		
		4x CD-ROM), or, Modular DVD-ROM Drive (8x DVD-ROM, 24x CD-ROM)		
udio		AC9228X5T AC'97-compliant codec with 20-bit audio; built-in dual array		
	digital microphones with IntelliSonic [™] noise cancellation and echo suppression			
Communication	Multinational 56K ³ V.90 ⁴ modem and 10/100/1000 Gigabit Ethernet LAN			
Vireless Communication	Intel® PRO/Wireless 3945ABG Network Connection (Tri-mode 802.11a/b/g) or Atheros Super AG® Wireless LAN (802.11a/b/g); Wi-Fi® certified; dual diversity antennas. Optional Bluetooth (v2.0) Personal Area Network (PAN) for file transfer and data synchronization with other Bluetooth devices			
Jser Interface	82-key keyboard, spill-resistant; touch pad with left, right, and scroll buttons			
Ports	Three USB 2.0, Infrared port (IrDA 1.1-compatible, 4 Mbps), External monitor/VGA			
	modem (RJ- connector, h	11), Gigabit Ethernet (RJ-45), SD/Memory Stick PRO slot, docking eadphone/line-out/optical digital (SPDIF) jack, and microphone/line-in jack		
Card Slots	One Type I/II PCMCIA slot, 32-bit PC CardBus architecture;			
	One Smart (
		slot for Memory Stick [®] , Memory Stick PRO™, or Secure Digital (SD) card		
Security	LifeBook Application/Security panel AuthenTec Fingerprint Sensor with TruePrint Technology; 15cm/sec slide speed Trusted Platform Module (TPM), TCG 1.2-compliant Dedicated Smart Card slot			
		nd BIOS passwords		
		rt for Computrace/LoJack Theft recovery system (Service required)		
	Security loci			
Battery⁵		r: Lithium ion (6-cell, 10.8V, 5200 mAh), 56.16 WHr)		
Jationy		/ battery: Lithium ion (6-cell, 10.8V, 3800 mAh, 41 WHr)		
		ry for warm swapping of primary battery		
		p to 6 hrs. with main battery; up to 10 hrs. using both main and modular bay batter		
C Adapter	Autosensing	100-240V AC, 80W, supplying 19V DC, 3.15A		
)imensions/Weight		< 1.1/1.4"; approx. 4.3 lbs. with weight saver		
Operating Temperature	41°F to 95°F/5°C to 35°C (ambient temperature); 20% to 85% relative humidity.			
eperating remperature	non-condensing			
Ion-Operating	-			
Temperature	5°F to 140°F	/-15°C to 60°C, 8% to 85% relative humidity, non-condensing		
Key Accessories		of accessories, visit www.shopfujitsu.com or call 1-800-FUJITSU		
	Port Replica	tor: Power/Suspend/Resume button, four USB 2.0, external video, DVI-D, 11), Gigabit Ethernet (RJ-45), docking connector, audio line-out		

Compliance and Service Information

Compliance	FCC Part 15B Class B and FCC Part 15C; IC ICES-003 Class B and RSS-210 UL-cUL Listed FCC Part 68; IC CS-03 CE Marking ENERGY STAR®
Warranty ⁶	One-or three-year International Limited Warranty on select corporate configurations; 24/7 technical support; Fujitsu extended service plans available.



888.912.3151 601.399.5077 (fax) www.Howard.com

 Preinstalled with a free 90-day trial version of Symantec Norton Internet Security 2006. The 90-day trial version is activated upon user's acceptance of software license agreement. After 90 days, the user must purchase a subscription from Symantec to download latest virus definitions.

must purchase a subscription from Symantec to download latest virus definitions. 2) One gigapyte (GB) = one billion bytes; accessible capacity will be less and actual capacity depends on the operating environment and formatting.

the operating environment and formatting. 3) The internal modems on all Fujitsu mobile computers from Fujitsu Computer Systems Corporation are only qualified for use with telephone systems in selected countries, including the United States and Canada. For a list of certified countries, please check http://www.computers.us.fujitsu.com/modems.

http://www.computers.us.fujitsu.com/modems. 4) Actual speeds over U.S. telephone lines vary, and are less than 56 Kbps due to the current FCC regulations and line conditions.

5) Battery life estimates reflect the results of BAPCo MobileMark2005 Productivity Workloads performed upon systems with battery life setting enabled. Actual battery life will vary based on screen brightness, applications used, features selected, power management settings, battery conditioning, and other customer preferences. DVD/CD-RW, DVD Writer, LAN, wireless LAN or hard drive usage may also have a significant impact on battery life.

6) Service and warranty turnaround time may vary by country and product. The International warranty is only valid for products purchased in North, Central, and South America.

Fujitsu, the Fujitsu logo, and LifeBook are registered trademarks of Fujitsu Limited. Microsoft, Windows and OneNote are registered trademarks of Microsoft Corporation. Centrino, Intel, Intel Core, the Centrino logo and the Intel logo are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. Atheros, the Atheros logo and Super AG are all registered trademarks of Atheros Communications. Memory Stick is a registered trademark and Memory Stick PRO is a trademark of Sony Corporation and/or its affiliates. Adobe Reader is a registered trademark of the Wireless Ethernet Compatibility Alliance (WECA). Norton AntiVirus is a registered trademark mentioned herein are the property of their respective owners Product description data represents Fujitsu design objectives and is provided for comparative purposes; actual results may vary based on a variety of factors. Specifications are subject to change without notice.

©2007 Fujitsu Computer Systems Corporation. All rights reserved. FPC65-3169-02 -1/07. 07.0067







