

MOTION™ C5

PRODUCT SPECIFICATIONS



Chassis · Magnesium-alloy internal frame

• Upper faceplate composed of disinfectant-resistant resin

Lower backplate composed of disinfectant-resistant resin

overmolded with Elastomer

• Intel® Centrino® mobile technology with the Intel® Core Solo Processor/Cache

Processor U1400 (2MB of L2 cache, 1.20GHz, 533MHz FSB)

 Windows Vista™ Business **Operating Systems**

• Microsoft® Windows® XP Tablet PC Edition

• Intel 945GM Chipset

Display • 10.4" XGA TFT LCD (1024 x 768)

· View Anywhere® option

· Intel Display Power Saving Technology (DPST)

• Intel 945GM Extreme Graphics controller Graphics

Rotation: 0°, 90°, 180°, 270°

· Maximum 256MB total with Intel Dynamic Video Memory Video RAM

Technology (DVMT)

Audio Controller · Azalia HD audio codec

• DDR2 533MHz SDRAM memory System Memory

Base configuration of 512MB

Upgradeable to maximum 1.5GB at point of purchase

System Storage • 1.8" Hard Disk Drive (HDD) with 30GB or 60GB capacity

• PCI bus master enhanced IDE • Supports Ultra ATA 66/100

Communications • Integrated Intel® PRO/Wireless 3945a/b/g network connection

· Optional Atheros 802.11a/b/g card available

· Integrated Bluetooth®

Audio · Motion Speak Anywhere® technology

· Multi-directional array microphone design with 2 microphones

· Knowles Acoustics IntelliSonic software

· Integrated speaker

I/O Ports Docking connector

• DC power-in port with rubberized cover

Embedded I/O • 2.0 Megapixel Camera

Optional 1D/2D Barcode Reader

13.56MHz RFID reader

• 13.56MHz HF integrated passive RFID tag

Security · Integrated Fingerprint Reader with OmniPass software

• TCG Trusted Platform Module (TPM) 1.2

• 10.0" x 10.0" x .95" (256mm x 256mm x 24.3mm) **Dimensions**

Weight 3.1 lbs.¹ (1.40 kg)

· Lithium-ion standard battery with 40WHr capacity Battery

Battery Charging Time Standard Battery - 1.5 hours (Tablet PC on/off)²

System Status LEDs · Power on/off LED ring around power button

· Battery status LED

 Wireless 802.11 LED · Bluetooth LED

• RFID LED adjacent to RFID read trigger

Control Buttons • One 5-way directional control button for navigation

· One function button, one Dashboard control button and two

programmable buttons

Secure Attention Sequence (SAS) button

· Camera capture button

• RFID read trigger button

· Barcode scan trigger button

AC Adapter 50W universal, 3-pin jack

· 100-240V 1.5a, 50-60Hz

Docking Station with Battery Charging Bay • Integrated 10/100 Ethernet LAN controller with RJ-45 connector

• 3 USB 2.0 ports

VGA port

· Charging bay for spare standard battery

System Software · Motion Dashboard control panel

Motion/Softex OmniPass™ Security software

· Infineon Security Platform Tools · Toshiba Bluetooth Software

· Optional Medical Pak DVD

• Temperature Environmental

- Operation: +5°C to +35°C - Storage: -20°C to +60°C

· Humidity

- Operating humidity: 8% to 80% without condensation

- Storage humidity: 8% to 90% without condensation Altitude

- Operation: Sea level 0 to 10K ft.

- Storage: Sea level 0 to 40K ft.

• Enclosure class - Rated IP-54

Standards · ACPI 2.0 compliant

Regulatory • AS/NZS 3548:1995 Class B

AS/NZS 2064:1997 (ISM)

AS/NZS 4771

AS/NZS 4268

• FCC Part 15 Subpart B Class B • FCC Part 15 Subpart C (2.4Ghz) • FCC Part 15 Subpart E (5Ghz)

· FCC Part 18 (ISM)

CAN/CSA ICES-003 Class B

• CAN/CSA RSS-210 Issue 5

• CAN/CSA C22.2 No. 601-1-2 (compliant with medical grade adapter)

CENELEC EN 55022 Class B (CISPR22)
CENELEC EN 55024 (CISPR24) • CENELEC EN 55011 (ISM)

 CENELEC EN 61326 (ISM Immunity) CENELEC EN 60601-1-2 (compliant with medical grade adapter)

• CENELEC EN 61000-3-2 • CENELEC EN 61000-3-3 • ETSI EN 301-893 • ETSI EN 300-328-2 • ETSI EN 301-489-1

• ETSI EN 301-489-17 • ETSI EN 300-330 • ETSI EN 301-489-1/-3

• R&TTE (89/336/EEC) & R&TTE (99/5/EC)

Safety · AS/NZS 3260:1997

• FCC/ANSI C63.41

• UL, CUL, CE (IEC/EN60950-1 A11/2004)

• UL, CUL, CE (IEC/EN60601-1) (compliant with medical grade adapter)

· CAN/CSA RSS-102 • FCC OET65 Supplement C ETSI EN 50361

 LVD (73/23/EEC) • EU Directive 2002/95/EC • EU Directive 2002/96/EC

Warranty · Standard 1-year warranty

· Multi-year options available



For more information visit www.Howard.com or call us at 888.912.3151

Preliminary specifications. Subject to change

*Weight represents approximate system weight measured with a 40WHr battery. Actual system weight may vary depending on component and manufacturing variability. *Approximate charging time. Validated charging from 5% to 90% with system on or system off.