Environment Monitors

\\\&\\	/,0/,	10/16)	/MO/2
			COS AN
	NgC/ Ng	Cy. Major	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\

•					<u> </u>		
On-Board Sensor	Temperature	•	•	•	•	•	•
	هٔ Humidity / Dew point	•	•	•	•		
	Airflow			•	•		
	Light Level			•	•		
On-))) Sound Level			•	•		
External Sensor	Digital Sensor Ports	2	1	5	5	4	4
	Maximum Digital Sensor Capacity	4	4	16	16	16	4
	0-5 VDC Analog Sensor Ports	0	4	3	3	6	0
	Optional Built-in PoE (\$30)	•	•			•	
Hardware Features	Built-in Alarm Buzzer				•	•	
	Dry-Contact Relay Outputs	0	1	0	0	3	0
	LCD Display w/ scrolling measurements				•	•	
	Rackmount 19" 1U		•	•	•	•	
	Temperature Regulated Fan						2
	Ethernet			10/	100		
Web Server	IPv6	•	•				
	HTTP / HTTPS	•	•	•	•	•	•
	DHCP	•	•	•	•	•	•
We	Network Time Protocol (NTP)	•	•	•	•	•	•
	Real Time Sensor Data Feeds	GUI, HTTP, HTTPS, SNMP					
	Sensor Data Logging & Graphing	•	•	•	•	•	•
	Data Logs	CSV, J	JSON		CSV,	XML	
	SNMP (v1, v2c, v3)	•	•	•	•	•	•
Firmware	Email & Email-to-SMS Alerts	•	•	•	•	•	•
	Alarm Escalations	•	•	•	•	•	•
	Alarm Repeat	•	•	•	•	•	•
	Alarm Delay	•	•	•	•	•	•
	Alarm Valid Hours	•	•	•	•	•	•
	Periodic Email Status Reports			•	•	•	•
	Office 365 Email Support	•	•				
	Display in Metric or US Measurements	•	•	•	•	•	•
	Multiple Languages	•	•	•	•	•	•
	Access Account Levels	3	3	3	3	3	3
	Encryption via TLS/SSL	•	٠	•	•	•	•
	Interface with IP Surveillance Cameras	•	•	•	•	•	•
	Remote Firmware Updates	•	•	•	•	•	•
Benefits	Free Technical Support and Firmware Updates	•	•	•	•	•	•
Bei	Warranty	1 Year Standard Warranty*					
Reg	Regulatory Compliance		<u> </u>	FC	Œ	N136	



Plug-n-Play Sensors:

Temperature**

Temperature/Humidity/Dew Point (GTHD)** Temperature/Humidity/Dew Point (GT3HD)** Temperature/Humidity/Dew Point/Airflow** Analog-to-Digital Converter (A2D)

Analog / Dry Contact Sensors:

Door Position (NO/NC)

Smoke Detector (NO/NC)

Flood Sensor (Conductivity)

Water Sensing Cable Kit (NO/NC)

Power Failure Sensor (0-5V)

Current Transducer 30/60/120A (0-5V)

Isolated Voltage Sensor (0-5V)

60 VDC Sensor (0-5V)

Accessories:

5-Port Splitter

PoE Splitter

PoE Injector

In-line Power Meter 15A

In-line Power Meter 20A

-48 VDC Power Supply

PSTN Auto-Dialer (Analog)

GSM Auto-Dialer (SIM card required)

Rack Shelves

Blanking Panels

IP Network Cameras:

Wide range of IP cameras supported

D-Link DCS-930L

ClosetAir™:

Duct Discharge Adapter



Data Center



Strategically monitor data center, server room and network closet environments to protect critical infrastructure and prevent system downtime, hardware damage and data loss.


Telecom



Monitor climate and power conditions within base transceiver stations, cell sites, and technical rooms to ensure your equipment is running in optimal conditions.



Monitor and validate temperature among various environments within healthcare facilities including hospitals, blood and tissue banks, laboratories and more. Our sensors are designed to monitor extreme temperatures and allow users to satisfy FDA 21 CFR Part 11 compliant reporting.



Our environment monitors enable users to strategically monitor cold-storage facilities among restaurants, cafeterias, grocery stores and warehouses across the globe to protect perishable inventory ensuring food quality and safety.

Monitor



Temperature



Humidity/Dew Point



Airflow



Light Sound



Door Position



Smoke



Water Leaks



Power Failure



Voltage



Amperage



Kilowatt-Hour(s)



Battery



Video Surveillance

Prevent



Equipment Failure



Downtime



Loss of Revenue



Loss of Reputation

Alerts **⊗ ® ® ® ® ®**



- Alert notifications via Email, SMS,* SNMP Traps and voice call* when user-adjustable thresholds are breached
- **Automation and control** of external devices

Variety of Environmental Monitors Available

ITWatchdogs by Geist environment monitors are used for a wide range of other applications including traffic control boxes, climatecontrolled storage, wine cellars, air-traffic control communications closets, research laboratories, stability chambers, greenhouses, livestock, poultry farms and museums. Our products are fully scalable to meet various special needs.

Free Tech Support







