

The Lumens[™] DC125 Flyer composes of a DC125 document camera and a DC-W50 wireless base that supports 2.4GHz and 5GHz wireless transmission with a distance of up to 49 feet or 15 meters. It is compatible with iPads, allowing users to present lessons and demonstrations from anywhere in the room. It's an innovative presentation tool for teaching, meeting, training, conferencing and other functions.

The DC125 Flyer supports high definition, Full HD 1080p, 30fps output resolutions and is suitable for any HD display and interactive whiteboard. With no joints, the highly flexible gooseneck enables a 360° viewing angle and object viewing from just 2 inches or 1.64 centimeters to observe objects with the finest of detail. Press one button to get the perfect image quality every time. The convenience and versatility of the Lumens[™] DC125 Flyer wireless document camera is unprecedented.




Lume

Main Feature

- No Cords
- Full HD 1080p, 30fps output resolution
- Supports 2.4GHz and 5GHz wireless transmission from distance up to 49 feet or 15 meters
- Supports wireless and HDMI transmission simultaneously
- Supports iPad with Ladibug[™] app
- Broadcast and share live images within your collaborative learning environment
- Hands-free auto focusing
- Object viewing from just 1.6 inches or 44cm to observe detail
- 360° viewing angle
- No joints, highly flexible gooseneck



More Details



Broadcast and Share Live Images Within Your Collaborative Learning Environment

The teacher and students can select the option to share a live image from their location in the classroom by using a Ladibug[™] with a DC-W50 wireless base. The image is displayed at the front of the classroom but also on the students laptop computers or iPads so they can study the material from where they are seated. This technology allows students to enhance their learning skills on a higher level.



Support Wireless Control with iPad

The DC125 Flyer supports IEEE802.11 2.4GHz and 5GHz wireless transmission from a distance of up to 49 feet or 15 meters. Using an iPad with the Lumens Ladibug™ app allows users to control the DC125 remotely. Presenters can use real-time annotation over a live image for optimal instruction and interaction.



Supports Wireless and HDMI-out Simultaneously

The DC125 Flyer supports wireless and HDMI-out transmission simultaneously. The high definition live image can be displayed to a projector or Full HD-TV making it a powerful presentation tool.

User Friendly Interface

All frequently used commands are designed into buttons on the camera base including lamp on-off, image freeze, capture, and image optimization to adjust sharpness, brightness, and focus for the best image quality in an instant.



Innovative joint-free gooseneck design ensures smooth movement without vibration; high flexibility allows an unbelievable 360° viewing angle to observe objects in detail.

Joint-free Gooseneck



Specifications


Wireless standard	IEEE 802.11 g/n	Close-up	4cm (1.6")
Wireless Working	2.4/5 GHz ISM radio band	Shooting Area Max.	420 x 315mm (16.5" x12.4") > A3 size
Frequency		Frame Rate	1080p 30fps
Transmission Distance	15m (49 feet)	Lamp Built-in LED	On Camera Head
Full Charge Required	3 hours (for 8 hours continuous operation)	Image Capture	Single or Continuous Capture
Power Consumption	8W (Maximum)	Auto Tune	Yes, image optimization
Zoom Capacity	Mechanical Zoom:8x, Digital Zoom:8x	Image Rotation	0°, 180°, Flip, Mirror
Output Resolution	XGA, SXGA, 720p, 1080p	AP/Client Mode	Yes
High Color Reproduction	ΔE*ab 8.58 (mean)	Free Lumens [™] Software	Supports PC Windows 8, 7, XP, Vista iOS, and Mac OSX; WIA and TWAIN
SNR	51dB		interface
Sharpness	MTF 864 lines	Package Content	DC125 Document Camera and DC-W50 Wireless Base
Output	Wireless and HDMI	Warranty	5 Year (Battery is 1 year)

User Interface

• DC125



• DC-W50



HDMI OUT Kensington Ethernet USB 2.0 DC IN Lock Port



