

QConnect 3

QConnect Wireless Screen Sharing Device







Not which cable to use!











Easier Presentations. Faster Screen Sharing.



A More Efficient Workplace.

SPECIFICATIONS

DATA RATE		
## 802.3u(100BASE-TX) WIRELESS CHANNEL DATA RATE DATA RATE	STANDARDS	
WIRELESS CHANNEL		
DATA RATE		11(US, Canada); 3(Europe); 14(Japan)
LAN: 10/100Mbps		Wireless: Up to 300Mbps
PCONFIG. Automatic: DHCP Manual: Static IP address		
P CONFIG. Manual: Static IP address	PROTOCOL	TCP/IP
MANAGEMENT Meb-based configuration, SNMP SECURITY IEEE Standard 64/128 bit WEP / WPA / WPA2-PSK ANTENNA Dipole 2dBi x 2 RECEIVER SENSITIVITY 11b: <-80dBm @ 11Mbps	IP CONFIG.	Automatic: DHCP
SECURITY IEEE Standard 64/128 bit WEP / WPA / WPA2-PSK		Manual: Static IP address
WEP / WPA / WPA2-PSK	MANAGEMENT	Web-based configuration, SNMP
Tible Suppose Tible	SECURITY	
Tig: <-70dBm @ 54Mbps	ANTENNA	Dipole 2dBi x 2
SENSITIVITY		11b: <-80dBm @ 11Mbps
11n: <-64dBm @ 802.11n (HT20) WIRELESS LINK COVERAGE		11g: <-70dBm @ 54Mbps
COVERAGE environment VGA: SVGA (800x600), XGA (1024x76 WXGA (1280x768), WXGA (1280x800), WXGA (1360x768), WXGA+ (1440x900) UXGA (1600x1200) BUPPORTED ACCOUNT RIGHTS Administrators, Limited User, Guest Mac OS X 10.5 and above WIFI-Doc & SidePad: Android 2.2 & above, iPad / iPhone OS 3.2 & above, iPad / iPhone OS 3.2 & above POWER External Power Adaptor 5V DC input 2. VGA HDMI RJ-45 USB 2.0 (3) Power Button Reset Button Stereo Phone Jack Power Dimension (L x W x H): 154 x 50.7 x 24mm Weight: 238g Operation temperature: -10°C ~ 60°C Operating humidity: ≤ 90%		11n: <-64dBm @ 802.11n (HT20)
SUPPORTED OUTPUT RESOLUTION VGA: SVGA (800x600), XGA (1024x76 WXGA (1280x768), WXGA (1280x800), WXGA (1360x768), WXGA+ (1440x900) UXGA (1600x1200) SUPPORTED ACCOUNT RIGHTS Administrators, Limited User, Guest Mac OS X 10.5 and above WFi-Doc & SidePad: Android 2.2 & above, iPad / iPhone OS 3.2 & above,		Up to 300 feet/100 meters, depends on environment
DAGA (1800X1200)	OUTPUT	VGA: SVGA (800x600), XGA (1024x768), WXGA (1280x768), WXGA (1280x800), WXGA (1360x768), WXGA+ (1440x900),
HDMI: 720 (1280x720) / 1080 (1920x1080)		, ,
SUPPORTED ACCOUNT RIGHTS SUPPORTED OPERATION SYSTEM Windows XP / Vista / 7 / 8 Mac OS X 10.5 and above WiFi-Doc & SidePad: Android 2.2 & above, iPad / iPhone OS 3.2 & above, iPad / iPhone OS 3.2 & above, iPad / iPhone OS 3.2 & above iPad / iPhon		
Mac OS X 10.5 and above WiFi-Doc & SidePad: Android 2.2 & above, iPad / iPhone OS 3.2 & above POWER External Power Adaptor 5V DC input 2. VGA HDMI RJ-45 USB 2.0 (3) Power Button Reset Button Stereo Phone Jack Power Dimension (L x W x H): 154 x 50.7 x 24mm Weight: 238g Operation temperature: 0 ~ 40°C Storage Temperature: -10°C ~ 60°C Operating humidity: ≤ 90%	ACCOUNT	
WiFi-Doc & SidePad: Android 2.2 & above, iPad / iPhone OS 3.2 & above POWER External Power Adaptor 5V DC input 2. VGA HDMI RJ-45 USB 2.0 (3) Power Button Reset Button Stereo Phone Jack Power Dimension (L x W x H): 154 x 50.7 x 24mm Weight: 238g Operation temperature: 0 ~ 40°C Storage Temperature: -10°C ~ 60°C Operating humidity: ≤ 90%		
VGA		WiFi-Doc & SidePad: Android 2.2 & above, iPad / iPhone OS 3.2 & above
HDMI	POWER	External Power Adaptor 5V DC input 2.6A
RJ-45 USB 2.0 (3) Power Button Reset Button Stereo Phone Jack	INTERFACE	VGA
USB 2.0 (3) Power Button Reset Button Stereo Phone Jack Power Dimension (L x W x H): 154 x 50.7 x 24mm Weight: 238g Operation temperature: 0 ~ 40°C Storage Temperature: -10°C ~ 60°C Operating humidity: ≤ 90%		HDMI
Power Button Reset Button Stereo Phone Jack Power Dimension (L x W x H): 154 x 50.7 x 24mm Weight: 238g Operation temperature: 0 ~ 40°C Storage Temperature: -10°C ~ 60°C Operating humidity: ≤ 90%		RJ-45
Reset Button Stereo Phone Jack Power Dimension (L x W x H): 154 x 50.7 x 24mm Weight: 238g Operation temperature: 0 ~ 40°C Storage Temperature: -10°C ~ 60°C Operating humidity: ≤ 90%		USB 2.0 (3)
Stereo Phone Jack Power Dimension (L x W x H): 154 x 50.7 x 24mm Weight: 238g Operation temperature: 0 ~ 40°C Storage Temperature: -10°C ~ 60°C Operating humidity: ≤ 90%		Power Button
LED Power Dimension (L x W x H): 154 x 50.7 x 24mm Weight: 238g Operation temperature: 0 ~ 40°C Storage Temperature: -10°C ~ 60°C Operating humidity: ≤ 90%		Reset Button
Dimension (L x W x H): 154 x 50.7 x 24mm Weight: 238g Operation temperature: 0 ~ 40°C Storage Temperature: -10°C ~ 60°C Operating humidity: ≤ 90%		Stereo Phone Jack
154 x 50.7 x 24mm Weight: 238g Operation temperature: 0 ~ 40°C Storage Temperature: -10°C ~ 60°C Operating humidity: ≤ 90%	LED	Power
Operation temperature: 0 ~ 40°C Storage Temperature: -10°C ~ 60°C Operating humidity: ≤ 90%		
ENVIRONMENTAL Storage Temperature: -10°C ~ 60°C Operating humidity: ≤ 90%		Weight: 238g
CONDITIONS Operating humidity: ≤ 90%		Operation temperature: 0 ~ 40°C
operating mannary = 0070	ENVIRONMENTAL	Storage Temperature: -10°C ~ 60°C
Storage humidity: ≤ 80%	CONDITIONS	Operating humidity: ≤ 90%
		Storage humidity: ≤ 80%
CERTIFICATE FCC, CE, NCC	CERTIFICATE	FCC, CE, NCC
WARRANTY 1 year	WARRANTY	1 year

FEATURES

- Share lessons with every device in the room (BYOD - bring your own device)
- Customize WiFi network name
- Connect multiple QConnects at once
- Control your computer with a mobile device
- Broadcast iOS device screen to computer, then wirelessly broadcast computer image to a display or whiteboard
- View 1-4 screens at once to compare files from different devices
- Connect over 30 computers & devices at once

PROJECT IOS, ANDROID & OTHER MOBILE DEVICES

Present confidently with full control in your hands!





MIRROR MODE

Control your projected computer screen from a mobile device!



CONNECT 30+ DEVICES

Wirelessly connect over 30 devices, switching easily between screens. (Up to four screens displayed at once.)

