


Medix KW

tangent



15", 19", or 22" Medical Computer



SPECIFICATIONS

Display	15.6" LCD, 1366 x 768 (16:9) 18.5" LCD, 1366 x 768 (16:9) 21.5" LCD, 1920 x 1080 (16:9) LED backlit LCD 4-Wire resistive touch (21.5" only available with multi-touch) Optional: PCAP multi-touch (2 pt)
Processor	Intel 6th Gen Core i3/i5 (fanless design)
Chipset	Intel Skylake U SOC
Operating System	Windows 10, Windows 7
Storage	1x 2.5" HDD/SSD Up to 2TB
Video	Intel HD Graphics 520
Memory	Up to 8GB DDR3L (1x SO-DIMM)
Audio	Integrated HD audio (Realtek) Integrated speakers
Network Interface	2x Gbit Ethernet (Realtek) NOTE: 2nd Gbit Ethernet not available if WiFi present
Wireless	Optional: * Intel Wireless AC-7260 & Bluetooth * Not available if 2nd LAN present
Power	System Input: 12-48V DC AC Adapter: Input: 100 – 240V AC Output: 19V, 4.74A
I/O Ports	4x USB 3.0 2x USB 2.0 4x Serial ports (RJ48 w/DB9 adapter) 1x RJ45 (LAN) 1x DVI-D (out) 1x VGA (out) Audio ports (line-in/out) NOTE: 4th Serial adapter not available if WiFi Present

Expansion Slots	1x Mini PCIe
Multimedia	2.0 Mpixel camera
I/O Devices	Optional: 2D Barcode scanner, IC card reader (smart card/CAC), MSR, RFID module
Special Features	TPM, watchdog timer
Dimensions / Weight	15.6": 15.6" W x 9.7" H x 1.9" D / 9.9 lbs 18.5": 18.3" W x 11.2" H x 1.9" D / 15.0 lbs 21.5": 21.1" W x 12.9" H x 1.9" D / 17.5 lbs
Enclosure	Cast aluminum chassis Fanless design IP54 Front Panel
Mounting	VESA 75
Accessories	Optional: Stand
Environmental	Operating temp: 32° - 95°F (0° - 35°C) Storage temp: -4° - 140°F (-20° - 60°C) Humidity: 20% - 85% non-condensing
Certification	FCC/CE Class A /LVD, EN60601-1-2 (EN60601-1-2:2007 + AC:2011) 4th Edition, UL60601-1 (ANSI/AMI ES60601-1:2005+1:9+A2:10) 3rd Edition, RoHS (2011-65EU), WEEE (2012-65EU), REACH (2015.JUN)
Limited Warranty	1-Year parts & labor, return to depot

Contact a HOWARDmed Technology Solutions representative for pricing and ordering information:



Toll Free: 888.912.3151
www.howard-medical.com