

AXIS A1601 Network Door Controller

Advanced access management in midsized and large systems

With door controllers from Axis, you install one smart, independent device by each door to create a scalable access control system. The open platform allows you to mix and match best-of-breed software and hardware, and enables easy integration with other systems such as video surveillance, intrusion detection, and time and attendance. AXIS A1601 Network Door Controller is ideal for advanced access management using a partner software, in mid-sized and large, multi-site installations. It has a powerful processor, expanded storage and memory, relays, and I/O ports. AXIS A1601 is powered by PoE+ and can also power connected equipment.

- > [Based on Axis open platforms](#)
- > [ONVIF Profile A and C compliant](#)
- > [UL 293 and UL 294 certified](#)
- > [Supports most reader types](#)
- > [Ease of installation and PoE+ support](#)



AXIS A1601 Network Door Controller

Door controller		General	
Readers	Up to 2 readers, RS485 (OSDP)/Wiegand, with supported card formats. OSDP Secure Channel supported. Integration with ASSA ABLLOY Aperio® and Simons Voss SmartIntego wireless lock technologies.	Casing	Aluminum Color: white NCS S 1002-B For repainting instructions of skin cover or casing and impact on warranty, contact your Axis partner.
Doors	1–2 doors ^a	Sustainability	PVC free
Credentials	Unlimited with third-party access management software depending on server capacity. Up to 70 000 credentials stored locally in a fallback scenario where connection to partner software is temporarily lost.	Memory	512 MB RAM, 1 GB Flash
Event history	100 000 first in, first out (FIFO)	Power	Power in: 10.5–28 V DC, max 36 W, or Power over Ethernet (PoE) IEEE 802.3at Type 2 Class 4. 12 V battery as backup. Relay: 2x relay NO/NC, max 2 A DC Power out lock: 2x 12/24 V DC, max 24 W Total power budget for peripheral devices (locks, readers etc.): 2100 mA at 12 V if powered by DC, 1300 mA at 12 V if powered by PoE Class 4
Access schedules	Unlimited or third-party software dependent	Connectors	RJ45 10BASE-T/100BASE-TX PoE Terminal blocks: DC power, 14 inputs/outputs, RS485/Wiegand, relay, battery. Detachable and color coded connectors for ease of installation. Wire size for connectors: CSA: AWG 28–16, CUL/UL: AWG 30–14
I/O interface		Operating conditions	-40 °C to 55 °C (-40 °F to 131 °F) Humidity 20–85% RH (non-condensing)
I/O functionality	Reader I/O DC output: 2x 12 V DC output, max 486 mA; 2x2 configurable supervised inputs/outputs (digital input: 0 to max 30 V DC; digital output: 0 to max 30 V DC, open drain max 100 mA) Reader data OSDP/RS485 half duplex, Wiegand Auxiliary DC output: 1x 12 V DC output, max 200 mA, 4x configurable inputs/outputs (digital input: 0 to max 30 V DC; digital output: 0 to max 30 V DC, open drain max 100 mA) Door connections 2x2 supervised inputs for door monitors and REX (digital input: 0 to max 30 V DC) External 2x configurable inputs/outputs for auxiliary equipment (digital input: 0 to max 30 V DC; digital output: 0 to max 30 V DC, open drain max 100 mA)	Storage conditions	-40 °C to 55 °C (-40 °F to 131 °F)
Network		Approvals	EMC EN 55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class A, KC KN35 Safety IEC/EN/UL 62368-1, UL 2043, UL 294, UL 293 Environment EN 50581 Others CSA C22.2 No. 205-1983
Security	Password protection, IP address filtering, HTTPS ^b encryption, IEEE 802.1X ^b network access control, digest authentication, user access log, centralized certificate management	Dimensions	175 x 175 x 60 mm (6 7/8 x 6 7/8 x 2 3/8 in)
Supported protocols	IPv4, IPv6, HTTP, HTTPS ^b , SSL/TLS ^b , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP ^c , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Weight	1.2 kg (2.6 lb)
System integration		Included accessories	Installation guide, mating connectors (mounted), grounding kit, cable ties
Application Programming Interface	Open API for software integration, including VAPIX [®] ; specifications at www.axis.com ONVIF [®] Profile C and ONVIF [®] Profile A, specification at onvif.org	Optional accessories	AXIS Access Card 1K AXIS T8133 Midspan 30 W 1-port AXIS T8128 PoE Splitter 24 V (requires 30 W midspan) AXIS T8129 PoE Extender AXIS T98A15-VE Surveillance Cabinet ^c For more accessories, see www.axis.com
Integration-ready	AXIS A91 Network I/O Relay Module Series AXIS A4010-E Reader AXIS A4011-E Reader ASSA Aperio RS485 Communication Hub SimonsVoss SmartIntego TCP/IP GatewayNode	Languages	English, German, French, Spanish, Italian, Polish, Dutch
Events		Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
Tamper detection	Removal of unit cover/tamper front Reader tamper Tilting, vibration	<p>a. Power consumption dependent; max load for locks, readers and other equipment is 24 W with PoE+ and 30 W with 10.5–28 V DC.</p> <p>b. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eyay@cryptsoft.com).</p> <p>c. In outdoor installations combining AXIS A1601 and AXIS T98A15-VE, the maximum allowed voltage is 30 V DC.</p>	
Event log	Configurable by time and topic	Environmental responsibility: axis.com/environmental-responsibility	
Event triggers	Tamper detection, power loss, network loss, configuration, door, event logger, hardware, input signal, schedule, system, time, virtual inputs through API		
Event actions	Notification: email, HTTP, HTTPS, TCP and SNMP trap External output activation, status LED		